



LED Industrieleuchte
 LED industrial luminaire


INROLED_50 Ecolab, 565 mm, 230V AC

| | |
|---------------|---------------|
| Artikel-Nr.: | 110110-03 |
| EAN: | 4260556624662 |
| Zolltarifnr.: | 94054039 |

| | |
|------------------------|---------------------------------------------------------------|
| Bestellnr.: | 110110-03 |
| Modell: | INROLED_50 |
| Bauform: | LED Rohrleuchte |
| Leuchtmittel: | SMD LED |
| Lampenleistung: | ~16 W |
| Lampenlichtstrom: | 2060 lm |
| Lampenlichtausbeute: | 127 lm/W |
| Lichtverteilung: | direkt |
| Lichtfarbe: | Tageslichtweiß (5200 - 5700K) |
| Anschlusswert Leuchte: | 220-240V AC ± 10%, 50-60 Hz |
| Betriebsgerät: | integriert |
| Anschluss Leuchte: | M12 S-kodiert |
| Schutzart: | IP67/IP69K |
| Schutzklasse: | I |
| Entblendung: | opalweiß |
| Abstrahlwinkel: | 100° |
| Betriebstemperatur: | -30... +30 °C |
| Farbwiedergabe (Ra): | > 80 |
| Lampenlebensdauer: | > 50.000 h |
| Material Abdeckung: | Polycarbonat, matt, splitterfrei mit Ecolab-Beschichtung |
| Höhe [B] x Breite [C]: | Ø 50 mm |
| Länge [A]: | 565 mm |
| Gewicht: | 950 g |
| Bruttogewicht: | 1150 g |
| Risikogruppe: | freie Gruppe |
| Befestigungszubehör: | Leuchtenhalter aus metalldektierbaren PP inklusive |
| Kennzeichnung: | CE |
| Gefertigt in: | Deutschland |
| Besonderheit: | Food+Beverage geeignet: Ecolab zertifiziert, HACCP-Zertifikat |



Lampenlebensdauer in Betriebsstunden (L80/B10)


LED Industrieleuchte
LED industrial luminaire



INROLED_50 Ecolab, 565 mm, 230V AC

| | |
|-------------------------------|---------------|
| Item number: | 110110-03 |
| EAN: | 4260556624662 |
| Customs tariff number: | 94054039 |

| | |
|-----------------------------------|-------------------------------------------------------------|
| Order number: | 110110-03 |
| Model: | INROLED_50 |
| Type: | LED tube luminaire |
| Illuminant: | SMD LED |
| Power consumption: | ~16 W |
| Lamp luminous flux: | 2060 lm |
| Lamp luminous efficiency: | 127 lm/W |
| Light distribution: | direct |
| Light colour: | daylight white (5200 - 5700K) |
| Connected load: | 220-240V AC ± 10%, 50-60 Hz |
| Power supply: | inbuilt |
| Connection (connector): | M12 connector S-type encoded |
| Degree of protection: | IP67/IP69K |
| Class of protection: | I |
| Glare-free | opal white |
| Beam angle (optics): | 100° |
| Operating temperature: | -30... +30 °C |
| Colour rendering (Ra): | > 80 |
| Lamps lifetime: | > 50,000 h |
| Cover material: | polycarbonate, milky, shatterproof with Ecolab coating |
| Height [B] x Width [C]: | Ø 50 mm |
| Length [A]: | 565 mm |
| Weight (net): | 950 g |
| Gross weight: | 1150 g |
| Risk group (DIN EN 62471): | free group |
| Mounting accessories: | incl. luminaire holder made of metal detectable PP |
| Marking: | CE |
| Made in: | Germany |
| Feature: | Food+Beverage suitable: Ecolab certified, HACCP certificate |



Lamps lifetime in operation hours (L80/B10)