



## LED Arbeitsplatzleuchte

### LED workplace luminaire





## UNILED SL, 295 mm, 24V DC, Abdeckung Opalweiß

<b>Artikelnr.:</b>	110914-11
<b>EAN:</b>	4260556620312
<b>Zolltarifnr.:</b>	94054099

<b>Bestellnr.:</b>	110914-11
<b>Modell:</b>	UNILED SL
<b>Bauform:</b>	LED System- und Arbeitsplatzleuchte
<b>Leuchtmittel:</b>	SMD LED
<b>Lampenleistung:</b>	~15 W
<b>Lampenlichtstrom:</b>	1617 lm
<b>Lampenlichtausbeute:</b>	131 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Tageslichtweiß (5200 - 5700K)
<b>Anschlusswert Leuchte:</b>	24V DC $\pm$ 10%
<b>Anschluss Leuchte:</b>	M12 A-kodiert
<b>Schutzart:</b>	IP50
<b>Schutzklasse:</b>	III
<b>Entblendung:</b>	opalweiß
<b>Abstrahlwinkel:</b>	100°
<b>Betriebstemperatur:</b>	-10... +60 °C
<b>Farbwiedergabe (Ra):</b>	> 85
<b>Lampenlebensdauer:</b>	> 60.000 h
<b>Material Gehäuse:</b>	Aluminium
<b>Material Abdeckung:</b>	Kunststoff matt
<b>Höhe [B] x Breite [C]:</b>	35 mm x 85 mm
<b>Länge [A]:</b>	295 mm / 325 mm
<b>Gewicht:</b>	500 g
<b>Bruttogewicht:</b>	850 g
<b>Risikogruppe:</b>	freie Gruppe
<b>Befestigungszubehör:</b>	optional
<b>Dimmbar:</b>	optional über Zubehör
<b>Kennzeichnung:</b>	CE, ETL Listed
<b>Gefertigt in:</b>	Deutschland
<b>Besonderheit:</b>	Ausleuchtung homogen, schatten- und blendfrei

Lampenlebensdauer in Betriebstunden (L80/B10)

LED Arbeitsplatzleuchte  
LED workplace luminaire



UNILED SL, 295 mm, 24V DC, opal white cover

Item number:	110914-11
EAN:	4260556620312
Customs tariff number:	94054099

Order number:	110914-11
Model:	UNILED SL
Type:	LED system luminaire and workplace lighting
Illuminant:	SMD LED
Power consumption:	~15 W
Lamp luminous flux:	1617 lm
Lamp luminous efficiency:	131 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC $\pm$ 10%
Connection (connector):	M12 A-type encoded
Degree of protection:	IP50
Class of protection:	III
Glare-free	opal white
Beam angle (optics):	100°
Operating temperature:	-10... +60 °C
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60,000 h
Housing material:	aluminium
Cover material:	Makrolon®
Height [B] x Width [C]:	35 mm x 85 mm
Length [A]:	295 mm / 325 mm
Weight (net):	500 g
Gross weight:	850 g
Risk group (DIN EN 62471):	free group
Mounting accessories:	optional
Dimmable:	via optional accessory
Marking:	CE, ETL Listed
Made in:	Germany
Feature:	homogeneous lighting, shadow- and glare-free

Lamps lifetime in operation hours (L80/B10)