

LED Arbeitsplatzleuchte




LED workplace luminaire



UNILED SL AC, 545 mm, 220-240V AC, M12-S, Abdeckung Mikroprismen

Artikel-Nr.: 110914-42
EAN: 4260556623504

Bestell-Nr.:	110914-42
Modell:	UNILED SL
Bauform:	LED System- und Arbeitsplatzleuchte
Leuchtmittel:	SMD LED
Lampenleistung:	~17 W
Lampenlichtstrom:	2060 lm
Lampenlichtausbeute:	127 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	220-240V AC ± 10%, 50-60 Hz
Betriebsgerät:	integriert
Anschluss Leuchte:	M12 S-kodiert
Schutzart:	IP50
Schutzklasse:	I
Entblendung:	Mikroprismen
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +60 °C
Farbwiedergabe (Ra):	> 80
Lampenlebensdauer:	> 50.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Kunststoff Mikroprismen
Höhe [B] x Breite [C]:	35 mm x 85 mm
Länge [A]:	545 mm / 575 mm
Gewicht:	900 g
Bruttogewicht:	1350 g
Risikogruppe (DIN EN 62471):	Gruppe 1
Befestigungszubehör:	optional
Dimmbar:	optional über Zubehör
Kennzeichnung:	CE, UKCA
Gefertigt in:	Deutschland
Besonderheit:	Hohe Lichtstreuung, universell einsetzbar



Lampenlebensdauer in Betriebsstunden (L80/B10)




LED Arbeitsplatzleuchte
LED workplace luminaire



UNILED SL AC, 545 mm, 220-240V AC, M12-S,
micro prisms cover

Item number: 110914-42
EAN: 4260556623504

Order number: 110914-42
Model: UNILED SL
Type: LED system luminaire and workplace lighting
Illuminant: SMD LED
Power consumption: ~17 W
Lamp luminous flux: 2060 lm
Lamp luminous efficiency: 127 lm/W
Light distribution: direct
Light colour: daylight white (5200 - 5700K)
Connected load: 220-240V AC \pm 10%, 50-60 Hz
Power supply: inbuilt
Connection (connector): M12 S-type encoded
Degree of protection: IP50
Class of protection: I
Glare-free micro prisms
Beam angle (optics): 100°
Operating temperature: -10... +60 °C
Colour rendering (Ra): > 80
Lamps lifetime: > 50,000 h
Housing material: aluminium
Cover material: micro prisms cover
Height [B] x Width [C]: 35 mm x 85 mm
Length [A]: 545 mm / 575 mm
Weight (net): 900 g
Gross weight: 1350 g
Risk group (DIN EN 62471): group 1
Mounting accessories: optional
Dimmable: via optional accessory
Marking: CE, UKCA
Made in: Germany
Feature: high light diffusion, universally applicable



Lamps lifetime in operation hours (L80/B10)