



**LED Maschinenleuchte**  
*LED machine luminaire*

**FIELDLED II Einbau, 1060 mm, 120°, 24V DC**

<b>Artikel-Nr.:</b>	113310-11
<b>EAN:</b>	4260556621142
<b>Zolltarifnr.:</b>	94054099

<b>Bestellnr.:</b>	113310-11
<b>Modell:</b>	FIELDLED II
<b>Bauform:</b>	LED Aufbauleuchte für Maschinen
<b>Leuchtmittel:</b>	SMD LED
<b>Lampenleistung:</b>	~72 W
<b>Lampenlichtstrom:</b>	9504 lm
<b>Lampenlichtausbeute:</b>	132 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Tageslichtweiß (5200 - 5700K)
<b>Anschlusswert Leuchte:</b>	24V DC $\pm$ 10%
<b>Anschluss Leuchte:</b>	M12 Sensorstecker A-kodiert
<b>Schutzart:</b>	IP69K
<b>Schutzklasse:</b>	III
<b>Entblendung:</b>	opalweiß
<b>Abstrahlwinkel:</b>	120°
<b>Betriebstemperatur:</b>	-30... +55 °C
<b>Farbwiedergabe (Ra):</b>	> 85
<b>Lampenlebensdauer:</b>	> 60.000 h
<b>Material Gehäuse:</b>	Aluminium
<b>Material Abdeckung:</b>	Sicherheitsglas gefrostet, sprungsicher
<b>Höhe [B] x Breite [C]:</b>	34 mm x 96 mm / 132 mm
<b>Länge [A]:</b>	1060 mm / 1096 mm
<b>Gewicht:</b>	4250 g
<b>Risikogruppe:</b>	freie Gruppe
<b>Bruttogewicht:</b>	4800 g
<b>Kennzeichnung:</b>	CE, ETL Listed
<b>Befestigungszubehör:</b>	inkl. FKM Dichtung
<b>Dimmbar:</b>	optional über Zubehör
<b>Gefertigt in:</b>	Deutschland
<b>Besonderheit:</b>	100% CNC geeignet, sehr lichtstark

Lampenlebensdauer in Betriebsstunden (L80/B10)



LED Maschinenleuchte  
LED machine luminaire



Recessed luminaire FIELDLED II Einbau, 1060 mm,  
120°, 24V DC

Item number:	113310-11
EAN:	4260556621142
Customs tariff number:	94054099

Order number:	113310-11
Model:	FIELDLED II
Type:	LED surface-mounted luminaire for machines
Illuminant:	SMD LED
Power consumption:	~72 W
Lamp luminous flux:	9504 lm
Lamp luminous efficiency:	132 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC $\pm$ 10%
Connection (connector):	M12 Sensor connector A-type encoded
Degree of protection:	IP69K
Class of protection:	III
Glare-free	opal white
Beam angle (optics):	120°
Operating temperature:	-30... +55 °C
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60,000 h
Housing material:	aluminium
Cover material:	Safety glass, frosted, shatterproof
Height [B] x Width [C]:	34 mm x 96 mm / 132 mm
Length [A]:	1060 mm / 1096 mm
Weight (net):	4250 g
Risk group (DIN EN 62471):	free group
Gross weight:	4800 g
Marking:	CE, ETL Listed
Mounting accessories:	inkl. FKM Dichtung
Dimmable:	via optional accessory
Made in:	Germany
Feature:	100% CNC approved, sehr lichtstark



Lamps lifetime in operation hours (L80/B10)