

LED Arbeitsplatzleuchte



LED workplace luminaire



UNILED II Gelenkarm, dimmbar, 5200-5700K, Leuchtenbreite 548 mm

| | |
|----------------------|---------------|
| Artikelnr.: | 120710-02 |
| EAN: | 4260556620282 |
| Zolltarifnr.: | 94054099 |

| | |
|--------------------------------|------------------------------------|
| Bestellnr.: | 120710-02 |
| Modell: | UNILED II Gelenkarm |
| Bauform: | LED Gelenkarmleuchte |
| Leuchtmittel: | SMD LED |
| Lampenleistung: | ~27 W |
| Lampenlichtstrom: | 3217 lm |
| Lampenlichtausbeute: | ca. 131 lm/W |
| Lichtverteilung: | direkt |
| Lichtfarbe: | Tageslichtweiß (5200 - 5700K) |
| Anschlusswert Leuchte: | 24V DC \pm 10% |
| Betriebsgerät: | Netzteil 110-240V AC inkl. |
| Anschluss Leuchte: | M12 A-kodiert |
| Anschlusswert Netzteil: | 100-240V AC |
| Anschluss Netzteil: | EURO Stecker zu M12 Steckverbinder |
| Schutzart: | IP40 |
| Schutzklasse: | III |
| Entblendung: | opalweiß |
| Abstrahlwinkel: | 100° |
| Betriebstemperatur: | -10... +60 °C |
| Farbwiedergabe (Ra): | > 85 |
| Lampenlebensdauer: | > 60.000 h |
| Material Gehäuse: | Aluminium / Kunststoff |
| Material Abdeckung: | Makrolon |
| Länge Kopf [A]: | 548 mm |
| Länge Gelenkarme: | 2x 400 mm |
| Gewicht: | 2250 g |
| Bruttogewicht: | 3950 g |
| Risikogruppe: | freie Gruppe |
| Befestigungszubehör: | Tischklemme inkl. |
| Dimmbar: | Dimmer mit Memory Funktion intern |
| Gefertigt in: | Deutschland |
| Besonderheit: | dimmbar, weite Ausladung |



Lampenlebensdauer in Betriebstunden (L80/B10)



LED Arbeitsplatzleuchte
LED workplace luminaire



**UNILED II Gelenkarm (adjustable arm), dimmable,
5200-5700K, luminaire head width 548 mm**

| | |
|-------------------------------|---------------|
| Item number: | 120710-02 |
| EAN: | 4260556620282 |
| Customs tariff number: | 94054099 |

| | |
|-----------------------------------|--------------------------------------|
| Order number: | 120710-02 |
| Model: | UNILED II Gelenkarm (adjustable arm) |
| Type: | LED adjustable arm luminaire |
| Illuminant: | SMD LED |
| Power consumption: | ~27 W |
| Lamp luminous flux: | 3217 lm |
| Lamp luminous efficiency: | ca. 131 lm/W |
| Light distribution: | direct |
| Light colour: | daylight white (5200 - 5700K) |
| Connected load: | 24V DC \pm 10% |
| Power supply: | included external PSU 100-240V AC |
| Connection (connector): | M12 A-type encoded |
| Connected load PSU: | 100-240V AC |
| Connection PSU: | EURO plug to connector M12 |
| Degree of protection: | IP40 |
| Class of protection: | III |
| Glare-free | opal white |
| Beam angle (optics): | 100° |
| Operating temperature: | -10... +60 °C |
| Colour rendering (Ra): | > 85 |
| Lamps lifetime: | > 60,000 h |
| Housing material: | aluminium / plastics |
| Cover material: | Makrolon® |
| Head width [A]: | 548 mm |
| Length adjustable arms: | 2x 400 mm |
| Weight (net): | 2250 g |
| Gross weight: | 3950 g |
| Risk group (DIN EN 62471): | free group |
| Mounting accessories: | included table clamp |
| Dimmable: | internal dimmer with memory function |
| Made in: | Germany |
| Feature: | dimmable, large radius |



Lamps lifetime in operation hours (L80/B10)