



LED-Arbeitsplatzleuchte

Product-Nr.	121012-01
EAN:	4260556623719
Model:	CENALED SPOT Flexarm
Order number:	121012-01
Model:	CENALED SPOT Flexarm
Type:	LED workplace light with gooseneck
Illuminant:	High Power LED
Power consumption:	~8,5 W
Lamp luminous flux:	1120 lm
Lamp luminous efficiency:	134 lm/W
Light distribution:	direct
Light colour:	neutral white (5000K)
Connected load:	24V DC \pm 10%
Power supply:	-
Connection (connector):	connection cable 3m (9,84ft), flexible, two open cable ends
Degree of protection:	IP67
Class of protection:	III
Beam angle (optics):	30°
Operating temperature:	-10... +50 °C (14... 122 °F)
Colour rendering (Ra):	>80
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium (powder finished)
Cover material:	safety glass, shatterproof
Flex arm length [A]:	500 mm (19,69")
base height:	59 mm (2,32")
Mounting:	screw-on base
Weight (net):	800 g (~28 oz)
Gross weight:	1400 g (~49 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	yes, via push button at the luminaire head, ON/OFF and dimming
Mounting accessories:	magnet holder plate optional
Made in:	Germany
Feature:	universal workplace light with high protection degree

