



LED-Arbeitsplatzleuchte

Product-Nr.	121012-02
EAN:	4260556623726
Model:	CENALED SPOT Gelenkarm

Order number:	121012-02
Model:	CENALED SPOT Gelenkarm
Type:	LED workplace light with adjustable arm
Illuminant:	High Power LED
Power consumption:	~8,5 W
Lamp luminous flux:	1120 lm
Lamp luminous efficiency:	134 lm/W
Light distribution:	direct
Light colour:	neutral white (5000K)
Connected load:	24V DC \pm 10%
Power supply:	-
Connection (connector):	connection cable 3m (9,84 ft), flexible, two open cable ends
Degree of protection:	IP67
Class of protection:	III
Beam angle (optics):	30°
Operating temperature:	-10... +50 °C (14... 122 °F)
Colour rendering (Ra):	>80
Lamps lifetime:	> 60.000 h (L80/B10)
Housing material:	aluminium (powder finished)
Cover material:	safety glass, shatterproof
Length articulated arms:	350 mm / 400 mm
base height:	59 mm (2,32")
Weight (net):	1350 g (~48 oz)
Gross weight:	2550 g (~90 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	yes, via push button at the luminaire head, ON/OFF and dimming
Mounting accessories:	magnet holder plate optional
Made in:	Germany
Feature:	universal workplace light with high protection degree

Abstand d=50 cm
 $E_{\text{top}} = 3114 \text{ lux}$
 $E_{\text{mid}} = 8584 \text{ lux}$
 $E_{\text{bot}} = 516 \text{ lux}$

