

LED Arbeitsplatzleuchte



LED workplace light



CENALED FLOOD Flexarm AC

Artikelnr.: 121210-11
EAN: 4260556626314

Bestell-Nr.:	121210-11
Modell:	CENALED
Bauform:	LED-Arbeitsleuchte
Leuchtmittel:	SMD-LED
Lampenleistung:	~9 W
Lampenlichtstrom:	1260lm
Lampenlichtausbeute:	150lm/W
Lichtverteilung:	direkt
Lichtfarbe:	5700K
Anschlusswert Leuchte:	100-305V AC \pm 10%, 50-60 Hz
Betriebsgerät:	integriert
Anschluss Leuchte:	Anschlussleitung mit Netzstecker
Schutzart:	IP65
Schutzklasse:	I
Abstrahlwinkel:	118° -> Halbwertswinkel
Betriebstemperatur:	-10... +50 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium (pulverlackiert)
Material Abdeckung:	Sicherheitsglas
Länge Flexarm [A]:	500 mm
Sockelhöhe (B):	88 mm
Befestigung:	Anschraubsockel
Gewicht:	~1600 g
Bruttogewicht:	~2200 g
Befestigungszubehör:	optional
Dimmbar:	ja, über Taster am Leuchtenkopf, Ein/Aus und Dimmen
Kennzeichnung:	CE, UKCA
Gefertigt in:	Deutschland



Lampenlebensdauer in Betriebstunden (L80/B10)



LED Arbeitsplatzleuchte
LED workplace light



CENALED FLOOD Flexarm AC

Item number: 121210-11
EAN: 44260556626314

Order number:	121210-11
Model:	CENALED
Type:	LED workplace light
Illuminant:	SMD-LED
Power consumption:	~9 W
Lamp luminous flux:	1260lm
Lamp luminous efficiency:	150lm/W
Light distribution:	direct
Light colour:	5700K
Connected load:	100-305V AC \pm 10%, 50-60 Hz
Power supply:	inbuilt
Connection (connector):	connection cable with power plug
Degree of protection:	IP65
Class of protection:	I
Beam angle (optics):	118° -> half value angle
Operating temperature:	-10... +50 °C
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60,000 h
Housing material:	aluminium (powder finished)
Cover material:	safety glass
Length Flexarm [A]:	500 mm
Base height (B):	88 mm
Mounting:	screw-on base
Weight (net):	~1600 g
Gross weight:	~2200 g
Mounting accessories:	optional
Dimmable:	yes, via push button at the light head, ON/OFF and dimming
Marking:	CE, UKCA
Made in:	Germany



Lamps lifetime in operation hours (L80/B10)