


LED Arbeitsplatzleuchte

LED workplace luminaire





SYSTEMLED Power, 472 mm, 4000-4500K, Abdeckung Mikroprismen

Artikel-Nr.:	141024-04
EAN:	4260556620503
Zolltarifnr.:	94054099

Bestellnr.:	141024-04
Modell:	SYSTEMLED
Bauform:	LED Systemleuchte
Leuchtmittel:	SMD LED
Lampenleistung:	~28 W
Lampenlichtstrom:	2678 lm
Lampenlichtausbeute:	131 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Neutralweiß (4000 - 4500K)
Anschlusswert Leuchte:	220-240V AC ± 10%, 50-60 Hz
Betriebsgerät:	integriert
Anschluss Leuchte:	Wieland GST18
Schutzart:	IP40
Schutzklasse:	I
Entblendung:	Prismenabdeckung
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +50 °C
Farbwiedergabe (Ra):	> 90
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Höhe [B] x Breite [C]:	40 mm x 138 mm
Länge [A]:	472 mm
Gewicht:	1800 g
Bruttogewicht:	2400 g
Risikogruppe:	freie Gruppe
Befestigungszubehör:	Befestigungswinkel inkl., sonst optional
Dimmbar:	optional über Zubehör
Kennzeichnung:	CE
Gefertigt in:	Deutschland
Besonderheit:	kaskadierbar


Abstand d=100 cm

 $E_{\text{min}} = 569 \text{ lux}$ $E_{\text{mit}} = 777 \text{ lux}$ $E_{\text{max}} = 318 \text{ lux}$ 

Elektrische Durchgangsverdrahtung (kaskadierbar): Mehrere Leuchten lassen sich elektrisch verketteten. An die erste Leuchte werden 230V AC angelegt und mit Wieland GST18 Leitungen (Zubehör) weitere Leuchten über Ein- und Ausgänge im Leuchtgehäuse miteinander verbunden. Die Gesamtstromstärke der verketteten Leuchten darf dabei nicht die Absicherung des betriebsseitigen 230V AC Anschlusses übersteigen.

Lampenlebensdauer in Betriebstunden (L80/B10)



LED Arbeitsplatzleuchte
LED workplace luminaire



**SYSTEMLED Power, 472 mm, 4000-4500K,
micro prisms cover**

Item number:	141024-04
EAN:	4260556620503
Customs tariff number:	94054099

Order number:	141024-04
Model:	SYSTEMLED
Type:	LED system luminaire
Illuminant:	SMD LED
Power consumption:	~28 W
Lamp luminous flux:	2678 lm
Lamp luminous efficiency:	131 lm/W
Light distribution:	direct
Light colour:	neutral white (4000 - 4500K)
Connected load:	220-240V AC ± 10%, 50-60 Hz
Power supply:	inbuilt
Connection (connector):	Wieland GST18
Degree of protection:	IP40
Class of protection:	I
Glare-free	microprism
Beam angle (optics):	100°
Operating temperature:	-10... +50 °C
Colour rendering (Ra):	> 90
Lamps lifetime:	> 60,000 h
Housing material:	aluminium
Height [B] x Width [C]:	40 mm x 138 mm
Length [A]:	472 mm
Weight (net):	1800 g
Gross weight:	2400 g
Risk group (DIN EN 62471):	free group
Mounting accessories:	mounting angle in delivery scope
Dimmable:	via optional accessory
Marking:	CE
Made in:	Germany
Feature:	cascadable



You can interlink several luminaires electrically (cascadable). 230V mains voltage is applied to the first luminaire and additionally Wieland extension cables are used to connect further luminaires to each other via the inputs and outputs in the luminaire housing. The total current of the interlinked luminaires must not exceed the fuse rating of the 230V connection on the operating side.

Lamps lifetime in operation hours (L80/B10)