



pofiled light with t-slot backsided

Product-Nr.	150614-07
EAN:	4260556626437
Model:	PROFILED AC
Order number:	150614-07
Model:	PROFILED AC
Type:	pofiled light with t-slot backsided
Illuminant:	SMD LED
Total output incl. driver:	~24 W
Power consumption:	~21 W
Lamp luminous flux:	3340 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	direct
Light colour:	5600K 3-step MacAdam
Connected load:	120-277V AC $\pm$ 10%, 50-60 Hz
Power supply:	inbuilt
Connection (connector):	Wieland GST18
Degree of protection:	IP40
Class of protection:	I
Glare control:	Microprisms
Beam angle (optics):	100°
Operating temperature:	-10 °C - +45 °C (14 °F - 113 °F)
Colour rendering (Ra):	>85
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	65 mm x 45 mm (~2,56" x ~1,77")
Length [A]:	900 mm (~35,43")
Weight (net):	1950 g (~69 oz)
Gross weight:	2650 g (~93 oz)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Mounting accessories:	optional
Made in:	Germany
Feature:	universal light

