



profiled light with t-slot backsided



|                                   |                                                  |
|-----------------------------------|--------------------------------------------------|
| <b>Product-Nr.</b>                | 150914-04                                        |
| <b>EAN:</b>                       | 4260556625393                                    |
| <b>Model:</b>                     | PROFILED AC                                      |
| Order number:                     | 150914-04                                        |
| <b>Model:</b>                     | PROFILED AC                                      |
| <b>Type:</b>                      | profiled light with t-slot backsided             |
| <b>Illuminant:</b>                | SMD LED                                          |
| <b>Total output incl. driver:</b> | ~41 W                                            |
| <b>Power consumption:</b>         | ~37 W                                            |
| <b>Lamp luminous flux:</b>        | 5678 lm                                          |
| <b>Lamp luminous efficiency:</b>  | ~155 lm/W                                        |
| <b>Light distribution:</b>        | Direct                                           |
| <b>Light colour:</b>              | 5700K 3-step MacAdam                             |
| <b>Colour rendering (Ra):</b>     | >85                                              |
| <b>Connected load:</b>            | 120-277V AC $\pm$ 10%, 50-60 Hz                  |
| <b>Power supply:</b>              | Integrated                                       |
| <b>Connection (connector):</b>    | 3 m (~9,84 ft.) connection cable with power plug |
| <b>Degree of protection:</b>      | IP40                                             |
| <b>Class of protection:</b>       | I                                                |
| <b>Glare control:</b>             | Microprisms                                      |
| <b>Beam angle (optics):</b>       | 100°                                             |
| <b>Operating temperature:</b>     | -10 °C - +45 °C (14 °F - 113 °F)                 |
| <b>Lamps lifetime:</b>            | > 100,000 h (L80/B10)                            |
| <b>Housing material:</b>          | aluminium                                        |
| <b>Cover material:</b>            | plastics                                         |
| <b>Height [B] x Width [C]:</b>    | 65 mm x 45 mm (~2,56" x ~1,77")                  |
| <b>Length [A]:</b>                | 1500 mm (~59,06")                                |
| <b>Weight (net):</b>              | 3840 g (~135 oz)                                 |
| <b>Gross weight:</b>              | 4640 g (~164 oz)                                 |
| <b>Risk group (DIN EN 62471):</b> | Free group                                       |
| <b>Markings:</b>                  | CE, UKCA                                         |
| <b>Mounting accessories:</b>      | Optional                                         |
| <b>Made in:</b>                   | Germany                                          |
| <b>Feature:</b>                   | universal light, dimmable                        |