

LED Maschinenleuchte



LED machine light



TUBELED_40 II integrated Power, 284 mm x 74 mm x 3 mm

Artikel-Nr.: 151010-03
EAN: 4260556625812

| | |
|-------------------------------------|--------------------------------------|
| Bestell-Nr.: | 151010-03 |
| Modell: | TUBELED_40 II Integrated |
| Bauform: | LED Einbauleuchte |
| Leuchtmittel: | SMD LED |
| Lampenleistung: | ~8 W |
| Lampenlichtstrom: | 1078 lm |
| Lampenlichtausbeute: | 131 lm/W |
| Lichtverteilung: | Light Forming Technology |
| Lichtfarbe: | Tageslichtweiß (5200 - 5700K) |
| Anschlusswert Leuchte: | 24V DC \pm 10% |
| Anschluss Leuchte: | M12 A-kodiert |
| Schutzart: | IP67/IP69K |
| Schutzklasse: | III |
| Entblendung: | Diffusor ESG |
| Abstrahlwinkel: | 100° |
| Betriebstemperatur: | -30... +60 °C |
| Farbwiedergabe (Ra): | > 85 |
| Lampenlebensdauer: | > 60.000 h |
| Material Gehäuse: | Aluminium |
| Material Abdeckung: | Sicherheitsglas, 4 mm |
| Höhe [B] x Breite [C]: | 32 mm x 74 mm, Blende 3 mm aufbauend |
| Länge [A]: | 284 mm (Blende) |
| Gewicht: | 550 g |
| Bruttogewicht: | 800 g |
| Risikogruppe (DIN EN 62471): | freie Gruppe |
| Kennzeichnung: | CE, UKCA, ETL Listed (5003526) |
| Dimmbar: | optional über Zubehör |
| Gefertigt in: | Deutschland |



Lampenlebensdauer in Betriebsstunden (L80/B10)



LED Maschinenleuchte
LED machine light



Recessed light TUBELED_40 II integrated Power,
284 mm x 74 mm x 3 mm

Item number: 151010-03
EAN: 4260556625812

Order number: 151010-03
Model: TUBELED_40 II Integrated
Type: LED recessed luminaire
Illuminant: SMD LED
Power consumption: ~8 W
Lamp luminous flux: 1078 lm
Lamp luminous efficiency: 131 lm/W
Light distribution: Light Forming Technology
Light colour: daylight white (5200 - 5700K)
Connected load: 24V DC \pm 10%
Connection (connector): M12 A-type encoded
Degree of protection: IP67/IP69K
Class of protection: III
Glare-free diffused safety glass
Beam angle (optics): 100°
Operating temperature: -30... +60 °C
Colour rendering (Ra): > 85
Lamps lifetime: > 60,000 h
Housing material: aluminium
Cover material: Safety glass, 4 mm
Height [B] x Width [C]: 32 mm x 74 mm, cover plate 3 mm externally
Length [A]: 284 mm (cover plate)
Weight (net): 550 g
Gross weight: 800 g
Risk group (DIN EN 62471): free group
Marking: CE, UKCA, ETL Listed (5003526)
Dimmable: optional via accessories
Made in: Germany



Lamps lifetime in operation hours (L80/B10)