




## FIELDLED EVO 1040\_96 Einbau, 1040 mm, 24V DC

**Artikel-Nr.:** 153310-11  
**EAN:** 4260556625553




<b>Bestell-Nr.:</b>	153310-11
<b>Modell:</b>	FIELDLED EVO 96 Einbau
<b>Bauform:</b>	LED Einbauleuchte für Maschinen
<b>Leuchtmittel:</b>	SMD LED
<b>Lampenleistung:</b>	~78 W
<b>Lampenlichtstrom:</b>	12000 lm
<b>Lampenlichtausbeute:</b>	155 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Tageslichtweiß (5200 - 5700K)
<b>Anschlusswert Leuchte:</b>	24V DC ± 10%
<b>Anschluss Leuchte:</b>	M12 Sensorstecker A-kodiert, stirnseitig
<b>Schutzart:</b>	IP67/IP69K
<b>Schutzklasse:</b>	III
<b>Entblendung:</b>	Mikroprismen
<b>Abstrahlwinkel:</b>	100°
<b>Betriebstemperatur:</b>	-30... +60 °C
<b>Farbwiedergabe (Ra):</b>	> 85
<b>Lampenlebensdauer:</b>	> 60.000 h
<b>Material Gehäuse:</b>	Aluminium
<b>Material Abdeckung:</b>	ESG (Sicherheitsglas), splitterfrei
<b>Höhe [B] x Breite [C]:</b>	30 x 96 mm, Rahmen: 5,6 x 132 mm
<b>Länge [A]:</b>	1040 mm, Rahmen: 1096 mm
<b>Gewicht:</b>	~3450 g
<b>Bruttogewicht:</b>	~4250 g
<b>Risikogruppe (DIN EN 62471):</b>	freie Gruppe
<b>Dimmbar:</b>	optional über Zubehör
<b>Kennzeichnung:</b>	CE, UKCA, ETL Listed (5003526)
<b>Gefertigt in:</b>	Deutschland



Abstand [m]	Kegeldurchmesser [m]	Beleuchtungsstärke [lx]
0.5	1.06	E(0°) 1790
	0.94	E(C90) 46.6° 3885
		E(CD) 43.2° 3445
1.0	2.11	E(0°) 4438
	1.88	E(C90) 46.6° 721
		E(CD) 43.2° 661
1.5	3.17	E(0°) 1972
	2.82	E(C90) 46.6° 321
		E(CD) 43.2° 383
2.0	4.23	E(0°) 1109
	3.76	E(C90) 46.6° 189
		E(CD) 43.2° 215
2.5	5.29	E(0°) 710
	4.70	E(C90) 46.6° 115
		E(CD) 43.2° 138
3.0	6.34	E(0°) 493
	5.63	E(C90) 46.6° 80
		E(CD) 43.2° 96

Abstand [m]      Kegeldurchmesser [m]      Beleuchtungsstärke [lx]

— C0 - C180 (Halbstrahlwinkel: 86.4°)  
 — C90 - C270 (Halbstrahlwinkel: 93.2°)



Lampenlebensdauer in Betriebsstunden (L80/B10)




## FIELDLED EVO 1040\_96 Einbau, 1040 mm, 24V DC

**Item number:** 153310-11  
**EAN:** 4260556625553




**Order number:** 153310-11  
**Model:** FIELDLED EVO 96 Einbau  
**Type:** LED recessed luminaire for machines  
**Illuminant:** SMD LED  
**Power consumption:** ~78 W  
**Lamp luminous flux:** 12000 lm  
**Lamp luminous efficiency:** 155 lm/W  
**Light distribution:** direct  
**Light colour:** daylight white (5200 - 5700K)  
**Connected load:** 24V DC ± 10%  
**Connection:** M12 sensor connector, A-type encoded, front-end  
**Degree of protection:** IP67/IP69K  
**Class of protection:** III  
**Glare-free** microprism  
**Beam angle (optics):** 100°  
**Operating temperature:** -30... +60 °C  
**Colour rendering (Ra):** > 85  
**Lamps lifetime:** > 60,000 h  
**Housing material:** aluminium  
**Cover material:** ESG (toughened safety glass), shatterproof  
**Height [B] x Width [C]:** 30 x 96 mm, frame: 5,6 x 132 mm  
**Length [A]:** 1040 mm, frame: 1096 mm  
**Weight (net):** ~3450 g  
**Gross weight:** ~4250 g  
**Risk group (DIN EN 62471):** free group  
**Dimmable:** via optional accessory  
**Marking:** CE, UKCA, ETL Listed (5003526)  
**Made in:** Germany



Abstand [m]	Kegeldurchmesser [m]		Beleuchtungsstärke [lx]	
0.5	1.06	0.94	E(0°)	17750
			E(C90)	3885
			E(CD)	3445
1.0	2.11	1.88	E(0°)	4438
			E(C90)	721
			E(CD)	661
1.5	3.17	2.82	E(0°)	1972
			E(C90)	321
			E(CD)	383
2.0	4.23	3.76	E(0°)	1109
			E(C90)	189
			E(CD)	215
2.5	5.29	4.70	E(0°)	710
			E(C90)	115
			E(CD)	138
3.0	6.34	5.63	E(0°)	493
			E(C90)	80
			E(CD)	96

— C0 - C180 (Halbstrahlwinkel: 86.4°)  
— C90 - C270 (Halbstrahlwinkel: 93.2°)



Lamps lifetime in operation hours (L80/B10)