



|                                   |                                             |
|-----------------------------------|---------------------------------------------|
| <b>Product-Nr.</b>                | 157210-01                                   |
| <b>EAN:</b>                       | 4260556627465                               |
| <b>Model:</b>                     | VARILED II Power                            |
| Order number:                     | 157210-01                                   |
| <b>Model:</b>                     | VARILED II Power                            |
| <b>Illuminant:</b>                | SMD LED                                     |
| <b>Power consumption:</b>         | 12 W                                        |
| <b>Lamp luminous flux:</b>        | 1899 lm                                     |
| <b>Lamp luminous efficiency:</b>  | 155 lm/W                                    |
| <b>Light distribution:</b>        | Direct                                      |
| <b>Light colour:</b>              | 5700K 3-step MacAdam                        |
| <b>Colour rendering (Ra):</b>     | >85                                         |
| <b>Connected load:</b>            | 24V DC $\pm$ 10%                            |
| <b>Power supply:</b>              | External                                    |
| <b>Connection (connector):</b>    | M8 A-coded                                  |
| <b>Number of poles:</b>           | 3                                           |
| <b>Degree of protection:</b>      | IP67                                        |
| <b>Class of protection:</b>       | III                                         |
| <b>Operating temperature:</b>     | -30 °C - +60 °C (-22 °F - 140 °F)           |
| <b>Storage temperature:</b>       | -20 °C - +80 °C (-4 °F - 176 °F)            |
| <b>Lamps lifetime:</b>            | > 100,000 h (L80/B10)                       |
| <b>Vibration resistance:</b>      | at 10 to 55 Hz (amplitude 0.35 mm (~0,01")) |
| <b>Shock resistance:</b>          | up to 50 g (~2 oz)                          |
| <b>Housing material:</b>          | aluminium and glass                         |
| <b>Height [B] x Width [C]:</b>    | 13,7 mm x 40,2 mm (~0,54" x ~1,58")         |
| <b>Length [A]:</b>                | 298 mm (~11,73")                            |
| <b>Mounting:</b>                  | direct                                      |
| <b>Weight (net):</b>              | 300 g (~11 oz)                              |
| <b>Gross weight:</b>              | 360 g (~13 oz)                              |
| <b>Risk group (DIN EN 62471):</b> | Free group                                  |
| <b>Markings:</b>                  | CE, UKCA, ETL Listed (5003529)              |
| <b>Dimmable:</b>                  | Optional via accessories                    |
| <b>Mounting accessories:</b>      | No                                          |
| <b>Made in:</b>                   | Germany                                     |