

LED Zubehör  
 LED accessories

 Sensor Kabel, 5 m, 4-Adern, offen/M12 Winkel-  
 buchse, A-kodiert

|                     |               |
|---------------------|---------------|
| <b>Artikel-Nr.:</b> | 200100-07     |
| <b>EAN:</b>         | 4260556621920 |

|                                |   |
|--------------------------------|---|
| <b>Bestell-Nr.:</b>            | 200100-07   |
| <b>Modell:</b>                 | LED2WORK Sensor Kabel 0,34 mm <sup>2</sup> , für 24V DC |
| <b>Bauform:</b>                | Sensor Kabel, PUR, schwarz                              |
| <b>Kodierung:</b>              | A-kodiert   |
| <b>Anzahl:</b>                 | 1   |
| <b>Länge Kabel:</b>            | 5 m   |
| <b>Kabelenden:</b>             | offene Enden, 4 Adern/ M12 Buchse, gewinkelt            |
| <b>Polzahl:</b>                | 4   |
| <b>Bemessungsspannung:</b>     | 250V  |
| <b>Strombelastung pro PIN:</b> | 4000 mA   |
| <b>Umgebungstemperatur:</b>    | -30...+90°C   |
| <b>Durchgangswiderstand:</b>   | < 0,005 Ω   |
| <b>Isolationswiderstand:</b>   | ≥=10 <sup>8</sup> Ω                                     |
| <b>Material Kabel:</b>         | PUR   |
| <b>Material Griffkörper:</b>   | Kunststoff, TPU, BK                                     |
| <b>Material Kontaktträger:</b> | Kunststoff, TPU, BK                                     |
| <b>Material Überwurf:</b>      | Metall, CuZn, vernickelt                                |
| <b>Material Dichtung:</b>      | FPM / FKM   |
| <b>Material Kontakte:</b>      | Metall, CuSn, vergoldet                                 |
| <b>Normen:</b>                 | IEC 61076-2-101   |
| <b>Befestigung an Leuchte:</b> | Steckverbinder M12 Buchse, gewinkelt                    |
| <b>RoHS:</b>                   | 1   |
| <b>UL:</b>                     | 1   |
| <b>Schutzart (montiert):</b>   | IP65, IP67, IP68  |
| <b>Gewicht:</b>                | 150 g   |
| <b>Bruttogewicht:</b>          | 200 g   |



## Sensor cable, 5 m, open, 4 cores/M12 socket, angled, A-type encoded

|                     |               |
|---------------------|---------------|
| <b>Item number:</b> | 200100-07     |
| <b>EAN:</b>         | 4260556621920 |

|                                       |   |
|---------------------------------------|---|
| <b>Order number:</b>                  | 200100-07   |
| <b>Model:</b>                         | LED2WORK sensor cable 0,34 mm <sup>2</sup> , for 24V DC |
| <b>Type:</b>                          | sensor cable, PUR, black                                |
| <b>Encoding:</b>                      | A-type encoded  |
| <b>Quantity:</b>                      | 1   |
| <b>Length of cable:</b>               | 5 m   |
| <b>Cable ends:</b>                    | open ends, 4 cores / M12 socket, straight               |
| <b>Number of contacts:</b>            | 4   |
| <b>Rated voltage:</b>                 | 250V  |
| <b>Current load per PIN:</b>          | 4000 mA   |
| <b>Operating temperature:</b>         | -30... +90°C  |
| <b>Resistance:</b>                    | < 0,005 Ω   |
| <b>Insulation resistance:</b>         | ≥10 <sup>8</sup> Ω                                      |
| <b>Material cable:</b>                | PUR   |
| <b>Materials grip body:</b>           | plastics, TPU, BK                                       |
| <b>Material contact carrier:</b>      | plastics, TPU, BK                                       |
| <b>Material cap:</b>                  | metal, CuZn, nickel-plated                              |
| <b>Material seals:</b>                | FPM / FKM   |
| <b>Materials contacts:</b>            | metal, CuSn, gold-plated                                |
| <b>Standards:</b>                     | IEC 61076-2-101   |
| <b>Gross weight:</b>                  | connector M12 socket, straight                          |
| <b>RoHS:</b>                          | 1   |
| <b>UL:</b>                            | 1   |
| <b>Degree of protection (fitted):</b> | IP65, IP67, IP68  |
| <b>Weight (net):</b>                  | 150 g   |
| <b>Gross weight:</b>                  | 200 g   |