


LED Zubehör
LED accessories

T-Stück M12 A-kodiert für 24V DC

Artikel-Nr.:	200200-03
EAN:	4260556621999

Bestell-Nr.:	200200-03
Bauform:	T-Stück
Kodierung:	A-kodiert
Geeignet für:	24V DC LED Leuchten
Anzahl:	1
Anschlussart:	geschraubt
Umgebungstemperatur:	-30... +80 °C
Isolationswiderstand:	$\geq 10^8 \Omega$
Material Überwurf:	Metall, CuZn, vernickelt
Material Kabeldose:	Kunststoff
Material Kontakte:	Metall, CuZn, vergoldet
Ausführung:	M12 Buchse auf M12 Stecker und M12 Buchse
Bemessungsspannung:	60V AC/DC
Betriebsspannung:	24V DC
Strombelastbarkeit:	4 A
Schutzart (montiert):	IP65, IP67, IP68
Gewicht:	50 g
Bruttogewicht:	100 g





T-piece M12 A-type coded for 24V DC

Artikel-Nr.: 200200-03
EAN: 4260556621999

Order number:	200200-03
Type:	T-piece
Encoding:	A-type encoded
Suitable for:	24V DC luminaires
Quantity:	1
Contact termination:	screw-fastened
Operating temperature:	-30... +80 °C
Insulation resistance:	$\geq 10^8 \Omega$
Material screwcap:	metal, CuZn, nickel-plated
Materials cable casing:	plastics
Materials contacts:	metal, CuZn, gold-plated
Version:	socket M12 to plug M12 and socket M12
Rated voltage:	60V AC/DC
Operating voltage:	24V DC
Current carrying capacity:	4 A
Degree of protection (fitted):	IP65, IP67, IP68
Rated voltage:	50 g
Operating voltage:	100 g

