


## Light holder



Langloch für M6 Schrauben  
Befestigungselemente Leuchtenseitig im Lieferumfang enthalten

|                                   |                                                            |
|-----------------------------------|------------------------------------------------------------|
| <b>Product-Nr.</b>                | 240400-05                                                  |
| <b>EAN:</b>                       | 4260556627533                                              |
| <b>Model:</b>                     | Lamp Holder SYSTEMLED EVO / PROFILED                       |
| <b>Order number:</b>              | 240400-05                                                  |
| <b>Model:</b>                     | Lamp Holder SYSTEMLED EVO / PROFILED                       |
| <b>Type:</b>                      | Light holder                                               |
| <b>Amount:</b>                    | 1 pair                                                     |
| <b>Suitable for:</b>              | SYSTEMLED EVO and PROFILED                                 |
| <b>Attachment to a luminaire:</b> | using a T-slot stone                                       |
| <b>Material:</b>                  | Steel                                                      |
| <b>Scope of delivery:</b>         | Holder, ESD decoupling, T-slot fastening on the light side |
| <b>Material:</b>                  | Material: Steel / electrostatic dissipative plastic        |
| <b>Dimensions (mm):</b>           | 134 mm x 41 mm x 5 mm (~5,28" x ~1,61" x ~0,2")            |
| <b>Attachment to luminaire:</b>   | via T-slot stone                                           |
| <b>Weight (net):</b>              | 150 g (~5 oz)                                              |
| <b>Gross weight:</b>              | 200 g (~7 oz)                                              |
| <b>Feature:</b>                   | ESD insulation                                             |
| <b>Note:</b>                      | Without fastening material on the T-slot profile           |