LR6-EX SERIES

CE & II 3 G Ex nA IIC T4 Gc, II 3 D Ex tc IIIC T80°C Dc IP65 2014/34/(ATEX): EN 60079-0:2012 / A11:2013, EN 60079-15:2010, EN 60079-31:2014

Ø60mm Signal Towers

The LR-EX Explosion Proof Signal Tower Series features up to five LED segments tightly secured together with screws to ensure compliance with certifications and to prevent tampering or loosening from continuous vibration. Each ultra-bright, maintenance free, LED unit is designed with intricately cut lenses with a double-reflection system to produce even, brilliant, light output, visible from further distances. The lenses and body structure is dust and water tight and constructed from durable polycarbonate to withstand harsh environments.

■ FEATURES

- Suitable for Zone 2 and Zone 22 applications
- CE compliance in accordance with ATEX
- Fully-enclosed sound module with 4 built-in sounds
- IP65 protection rating

OPTIONS

- 3/4" NPT pole mount or direct mount adapter
- Wall mount brackets







Dimensions (mm)

Signal Tower LR6: φ60 1 Tier: 173.5 2 Tiers: 213.5 3 Tiers: 253.5 4 Tiers: 293.5 5 Tiers: 333.5 (90)

WALL MOUNT BRACKET






Specifications

Explosion-safety	(€ ₺ II 3 G Ex nA IIC T4 Gc, II 3 D Ex tc IIIC T80°C IP65		
CE conformities	EN 60079-0, EN 60079-15, EN 61241-0, EN 61241-1		
Certification	EC-Declaration of conformity		
Ambient Temperature	-20 °C to +50 °C		
Ingress Protection	IP65 to EN 60529		
Material	Polycarbonate		
Lighting Source	A Uniform 360° Light-Emitting Design		
Acoustical Source	85 dB (at 1m) with 4 sound options		
Rated Voltage	24V DC (PNP/NPN No Polarity)		
Module Colors Available	Red, Amber, Green, Blue, Clear/white		
Cable	Jacketed cable, Ø8mm, 3m length		

	CURRENT	RATINGS		
LED		BUZZER		
LL	.0	502	-2-11	
Signal Lir	e Current		Inruch Current	
Red, Amber	Green, Blue, Clear	Signal Line Current	Inrush Current	
approx. 40 mA		approx. 40 mA	approx. 250 mA	



Lighting/Flashing/Alarm 24V DC External Contact Classification Voltage Contact Relay LED Gre Audible FD Blue LED Whit e /6 * Fuse 1A 24 V DC (Clas

Model Code

Lighting 24V DC

LR6-502WJBU-RYGBC-EX

Tiers Rated Voltage 02 24V DC

⊕ ⊖ ⊖ 24 V DC (Class 2) (No polarity)

DO ITTODO EX							
Buzzer LED Module Color							
	N	Continuous Lighting			R	Red	
	В	Audible			Υ	Amber	
D. I. I. O. I.			G	Green			
- Bracket Code				В	Blue		
WJ	-	Wall Mount			С	Clear / White	
NJ	NPT Adaptor			(Top to bottom)			